# All-round spray

High-performance maintenance and service product for all applications in the fields of industry, trade, household and hobby, acts as a corrosion protection on metal parts, as a penetrating oil (rust remover, elimination of squeaking and creaking noises), as a water displacing agent, as a lubricant and as a cleaner (including oil, grease, tar and adhesive residue), leaves behind a long-lasting adhesive film that neither smears nor sticks. Ideal application in the field of electrical engineering and electronics as an anti condensation agent on circuit boards, as a contact spray on generators and solenoid switches.

	 /	
400 ml	12	15 1120
50 ml	12	15 1122



special testing gas for the quick and reliable functional testing of photoelectric (optoelectronic) smoke detectors without complex testing equipment. Tin content sufficient for approx. 150 smoke detector tests.

# Cimco Nuclearities for the second se

# Altound-Sprov

### **Adhesives**

# Assembly adhesive

for the quick, universal bonding of metals, various plastics, concrete, marble, natural and artificial stone, ceramics, enamel, plaster as well as MDF board, wooden board, chipboard, fibreboard and plasterboard. Thanks to its solid consistency, it is possible to bond cable channels in areas where drilling is not possible (e.g. on wall and ceiling) without any problems whatsoever. The assembly adhesive is silicone and solvent free and can be coated / painted over ("wet on wet").

white	310 ml	12	15 1154
grey	310 ml	12	15 1156



transparent 2-component adhesive with extremely good adhesive properties, elastic as well as impact/tension/shock resistant, for all materials.

,,				
	24 g	12	15 1210	



steel-filled 2 component epoxy minute adhesive, high impact and tensile strength, temperature resistant from  $-60\,^{\circ}\text{C}$  to  $+145\,^{\circ}\text{C}$ .

24 g 12 15 121



premium adhesive and sealant for the securing, fastening and sealing of screws, studs, joint and surface connections. Hardening takes place following metal contact with the air. Medium-strength, for gap bridging between 0.05 mm and a max. of 0.25 mm.

1	0	0 ,	0 1	0 0	
		24 ml		12	15 1224

### Universal instant adhesive

solvent-free and cold-setting cyanoacrylate adhesive that hardens under pressure.

0 / /				
	20 g	12	15 1200	
	U			

### **Silicone**

1 component adhesive and sealant, bonds to the majority of sub-surfaces such as aluminium, steel, glass, glass fabric, ceramic, plastic, wood and many other materials.

transparent	310 ml	12	15 1260
white	310 ml	12	15 1262
grey	310 ml	12	15 1264

# Metal sprays

### Zinc spray

durable, quick-drying cathodic corrosion protection with long-term effect for all metal surfaces, resistant against salt, water and heat up to approx.  $500\,^{\circ}$ C, suitable for the improvement of damaged zinc layers.

	400 ml	12	15 1100
light	400 ml	12	15 1102

### **Aluminium spray**

99.5% pure aluminium, long-term heat resistant protection up to +800 °C, bonds to almost all materials such as steel, non-ferrous metal, wood, cardboard, plastic, ceramic, etc. resistant against weathering.

non-ferrous metal, woo	od, cardboard, plastic, cer	amıc, etc. resistant aga	inst weathering.		
		400 ml	12	15 1110	

### Stainless steel spray

corrosion-resistant and effective surface coating, securely bonds to all metals, glass, wood, stone, cardboard and the majority of plastics.

	400 ml	12	15 1114	
Design	Size mm	PU	Article no.	











