

Product Specification Sheet



Technical Information

| Instant Start: | 0-100% in lt1s | \$ IP Rating: | IP20 |
|----------------|----------------|------------------------|--------------|
| EQ-WATTS: | 60 | Dimmable: | No |
| Watts: | 10 | Warranty (Years): | 2 |
| Lumens: | 750 | PF: | >0.5 |
| Beam Angle: | 120 | CRI: | >80 |
| Unit Color: | White | Operation Temperature: | -25 to +50°c |
| Body Type: | Aluminium | Input Power: | AC:85-265V, |
| Long life: | 30,000 Hours | Sensor Compatibility: | Yes |
| LED Chip Type: | EPISTAR | | |

Features

- Efficient High quality LED Chips & Integrated Driver
- PC Diffuser for Optimized light distribution and ambiance
 - High Impact Iron body with attractive white finish
 - Light weight structure for easy installation on false ceilings & building structures
 - Application : Commercial Offices and Work stations, Corridors



Suitable & Recommended for maximum daily use of 10-12 hours, usage beyond this would void the warranty

Packaging

| | | Listing Details | |
|---------------------------------|---------|-----------------|---------------|
| Gross Weight(GW) Kgs | 0.32 | EAN Code | 3800157626637 |
| Length(Box)mm | 60 | Commodity Code | 9405403990 |
| Width(Box)mm | 175 | | |
| Height(Box)mm | 80 | | |
| Unit CBM | 0.00107 | | |
| Master Box Packaging | | | |
| Master Box Qty (Pcs Per Carton) | 20 | | |
| Qty Per Pallet | 1200 | | |

