

SMOOTH WALLS - IP55 AND IP56

GW44234



JUNCTION BOXES WITH PLAIN QUICK FIXING LID - IP55 - GREY RAL 7035



Code	Internal dim. LxHxD (mm)	Max Ø holes possible	Lid screws (no. and type)	Characteristics	Pack. Carton.
GW 44 234	100x100x50	29 mm	4 insul. a 1/4 turn	Halogen Free	105
GW 44 236	150x110x70	29 mm	4 insul. a 1/4 turn	Halogen Free	50

NOTES: to restore the double insulation and the original IP degree of protection of the boxes, use the screwcaps in insulating material, or the brackets for wall mounting.

GW44207



JUNCTION BOXES WITH PLAIN, SCREWED LID - IP56 - GREY RAL 7035



Code	Internal dim. LxHxD (mm)	Max Ø holes possible	Lid screws (no. and type)	Characteristics	Pack. Carton.
GW 44 204	100 x 100 x 50	29 mm	4 - Stainless steel	Halogen Free	105
GW 44 205	120 x 80 x 50	29 mm	4 - Stainless steel	Halogen Free	91
GW 44 206	150 x 110 x 70	29 mm	4 - Stainless steel	Halogen Free	50
GW 44 207	190 x 140 x 70	37 mm	4 insul. sealable hinged	Halogen Free	30
GW 44 208	240 x 190 x 90	37 mm	4 insul. sealable hinged	Halogen Free	14
GW 44 209	300 x 220 x 120	48 mm	4 insul. sealable hinged	Halogen Free	6
GW 44 210	380 x 300 x 120	48 mm	4 insul. sealable hinged	Halogen Free	4
GW 44 211	460 x 380 x 120	48 mm	6 insul. sealable hinged	Halogen Free	3

ACCESSORIES SUPPLIED: GW44211, screwcaps for double insulation.

NOTES: to restore the double insulation and the original IP degree of protection of the boxes, use the screwcaps in insulating material, or the brackets for wall mounting.

GW44217



JUNCTION BOXES WITH DEEP, SCREWED LID - IP56 - GREY RAL 7035



Code	Internal dim. LxHxD (mm)	Max Ø holes possible	Lid screws (no. and type)	Characteristics	Pack. Carton.
GW 44 214	100 x 100 x 120	29 mm	4 - Stainless steel	Halogen Free	45
GW 44 215	120 x 80 x 120	29 mm	4 - Stainless steel	Halogen Free	55
GW 44 216	150 x 110 x 140	29 mm	4 - Stainless steel	Halogen Free	24
GW 44 217	190 x 140 x 140	37 mm	4 insul. sealable hinged	Halogen Free	16
GW 44 218	240 x 190 x 160	37 mm	4 insul. sealable hinged	Halogen Free	12
GW 44 219	300 x 220 x 180	48 mm	4 insul. sealable hinged	Halogen Free	7
GW 44 220	380 x 300 x 180	48 mm	4 insul. sealable hinged	Halogen Free	3
GW 44 221	460 x 380 x 180	48 mm	6 insul. sealable hinged	Halogen Free	2

ACCESSORIES SUPPLIED: GW44221, screwcaps for double insulation.

NOTES: to restore the double insulation and the original IP degree of protection of the boxes, use the screwcaps in insulating material, or the brackets for wall mounting.