




**Main switch, 240 V, 125A, 1HP**

<b>Part no.</b>	<b>IS-125/1</b>
<b>Article no.</b>	<b>276286</b>
<b>Catalog No.</b>	<b>IS-125/1</b>



## Delivery programme

Basic function			Main load disconnect switch
Pole			1 pole
Application			Switchgear for industrial and commercial applications
Rated current	$I_n$	A	125
Product range			IS
Contact sequence			

### Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-5
Operating ambient temperature max.		°C	40

## Technical data ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)			
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ec1@ss8.1-27-14-23-01 [AFZ813011])			
Switching function			-

Number of normally open contacts		0
Number of normally closed contacts		0
Number of change-over contacts		0
Number of poles		1
Nominal rated current	A	125
Nominal rated voltage	V	240
Min. rated voltage	V	240
Rated switching capacity	kA	0
Short-circuit breaking capacity (I <sub>cw</sub> )	kA	2
Voltage type		AC
Forced segregation (according to DIN VDE 0113)		No
With signal lamp		No
Colour calotte		Not applicable
Lamp type		Not applicable
Lamp socket		Not applicable
Max. lamp power	W	0
Width in number of modular spacings		1
Built-in depth	mm	69.5
Degree of protection (IP)		IP40

## Dimensions

