

Residual Current Devices FRCdM Type G/B

Surge current-proof 3 kA, AC-DC sensitive, Type G/B (ÖVE E 8601)   

	$I_n/I_{\Delta n}$ (A)	Operating frequency (Hz)	Type Designation	Article No.	Units per package
4-pole					
25/0.03	50		FRCdM-25/4/003-G/B	167892	1/30
25/0.3	50/60		FRCdM-25/4/03-G/B	167896	1/30
40/0.03	50		FRCdM-40/4/003-G/B	167893	1/30
40/0.3	50/60		FRCdM-40/4/03-G/B	167897	1/30
63/0.03	50		FRCdM-63/4/003-G/B	167894	1/30
63/0.3	50/60		FRCdM-63/4/03-G/B	167898	1/30

SG49812



Residual Current Devices FRCdM Type S/B

Selective + surge current-proof 5 kA, Type S/B   

	$I_n/I_{\Delta n}$ (A)	Operating frequency (Hz)	Type Designation	Article No.	Units per package
4-pole					
25/0.3	50		FRCdM-25/4/03-S/B	167900	1/30
40/0.3	50		FRCdM-40/4/03-S/B	167901	1/30
63/0.3	50		FRCdM-63/4/03-S/B	167902	1/30

SG49812



Residual Current Devices FRCdM Type G/Bfq

Surge current-proof 3 kA, AC-DC sensitive, Type G/Bfq (ÖVE E 8601)   

	$I_n/I_{\Delta n}$ (A)	Operating frequency (Hz)	Type Designation	Article No.	Units per package
4-pole					
25/0.03	50		FRCdM-25/4/003-G/Bfq	179530	1/30
25/0.3	50/60		FRCdM-25/4/03-G/Bfq	167904	1/30
40/0.03	50		FRCdM-40/4/003-G/Bfq	179531	1/30
40/0.3	50/60		FRCdM-40/4/03-G/Bfq	167905	1/30
63/0.03	50		FRCdM-63/4/003-G/Bfq	179532	1/30
63/0.3	50/60		FRCdM-63/4/03-G/Bfq	167906	1/30

SG49812



Residual Current Devices FRCdM Type S/Bfq

Selective + surge current-proof 5 kA, Type S/Bfq   

	$I_n/I_{\Delta n}$ (A)	Operating frequency (Hz)	Type Designation	Article No.	Units per package
4-pole					
25/0.3	50		FRCdM-25/4/03-S/Bfq	167908	1/30
40/0.3	50		FRCdM-40/4/03-S/Bfq	167909	1/30
63/0.3	50		FRCdM-63/4/03-S/Bfq	167910	1/30

SG49812

