

Seria OPTIMA

Normy: EN 60309-1, EN 60309-2

GNIAZDA NATYNKOWE
KOMBI - IP44

Gniazdo natynkowe FRENCH STANDARD

	Opis	Opakowanie	Nr katalogowy
16A	2P+E (průmyslová) + 2P+E	6h 50/60 Hz 1/10	513.1653-FN
	3P+E + 2P+E	6h 50/60 Hz 1/10	513.1656-FN
	3P+N+E + 2P+E	6h 50/60 Hz 1/10	513.1657-FN
32A	2P+E (průmyslová) + 2P+E	6h 50/60 Hz 1/10	513.3253-FF
	3P+E + 2P+E	6h 50/60 Hz 1/10	513.3256-FF
	3P+N+E + 2P+E	6h 50/60 Hz 1/10	513.3257-FF

Gniazdo natynkowe GERMAN STANDARD

	Opis	Opakowanie	Nr katalogowy
16A	2P+E (průmyslová) + 2P+E	6h 50/60 Hz 1/10	513.1653-DN
	3P+E + 2P+E	6h 50/60 Hz 1/10	513.1656-DN
	3P+N+E + 2P+E	6h 50/60 Hz 1/10	513.1657-DN
32A	2P+E (průmyslová) + 2P+E	6h 50/60 Hz 1/10	513.3253-DF
	3P+E + 2P+E	6h 50/60 Hz 1/10	513.3256-DF
	3P+N+E + 2P+E	6h 50/60 Hz 1/10	513.3257-DF

Seria OPTIMA

Normy: EN 60309-1, EN 60309-2

WTYCZKI - IP67



Proste

	Opis	Kolor	Opakowanie	Nr katalogowy
63A	2P+ E 6h 50/60 Hz 200-250V		6/24	218.6333
	3P+ E 6h 50/60 Hz 380-415V		6/24	218.6336
	3P+N+E 6h 50/60 Hz 346-415V		6/24	218.6337
125A	2P+ E 6h 50/60 Hz 200-250V		1/8	218.12533
	3P+ E 6h 50/60 Hz 380-415V		1/8	218.12536
	3P+N+E 6h 50/60 Hz 346-415V		1/8	218.12537

GNIAZDA PRZENOŚNE- IP67



Proste

	Opis	Kolor	Opakowanie	Nr katalogowy
63A	2P+ E 6h 50/60 Hz 200-250V		6/24	318.6343
	3P+ E 6h 50/60 Hz 380-415V		6/24	318.6346
	3P+N+E 6h 50/60 Hz 346-415V		6/24	318.6347
125A	2P+ E 6h 50/60 Hz 200-250V		1/8	318.12543
	3P+ E 6h 50/60 Hz 380-415V		1/8	318.12546
	3P+N+E 6h 50/60 Hz 346-415V		1/8	318.12547