

Product Specification Sheet



Technical Information

Vatts: 36 umens: 3400 ueam Angle: 120 Init Color: White kody Type: ABS + Plastic ong life: 30,000 Hours
Beam Angle: 120 PF: Init Color: White CRI: Kody Type: ABS + Plastic Operation Temperature:
Jnit Color: White CRI: Xody Type: ABS + Plastic Operation Temperature:
ody Type: ABS + Plastic Operation Temperature:
a life: 30.000 Hours Input Power:
ED Chip Type: SMD2835 Sensor Compatibility:

Features

- Waterproof fittings inclusive of T8 LED Tubes
- Transparent PC diffuser with higher light transmittance
- Opaque ABS housing with good mechanical performance
- PG11 waterproof cable gland available for wiring input on one side of the housing
- Silicon gel gasket and PC clips ensuring IP65 protection
- Available in 120 cm and 150 cm
 - Long Lifespan, Low maintenance and energy saving
 - Applications Parking Lots, Warehouses, Garages, Storage Docks, Workshops and many more



Suitable & Recommended for maximum daily use of 10-12 hours, usage beyond this would void the warranty

Packaging

Unit Details		Listing Details	
Gross Weight(GW) Kgs	1.33	EAN Code	3800157626385
Length(Box)mm	1320	Commodity Code	9405403990
Width(Box)mm	120		
Height(Box)mm	60		
Unit CBM	0.009504		
Master Box Packaging			
Master Box Qty (Pcs Per Carton)	10		
Qty Per Pallet	100		

