

Rittal – The System.

Faster – better – everywhere.

Wall-mounted cooling units TopTherm "Blue e" Total cooling output 2.00 – 4.00 kW – SK 3329.500

Date : Dec 31, 2014

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-mounted cooling units TopTherm "Blue e" Total cooling output 2.00 – 4.00 kW – SK 3329.500

created : 31.12.2014 on www.rittal.com/com-en



Product description

Material: Sheet steel

Colour: RAL 7035

**Protection category
IP to IEC 60 529:** External circuit IP 34
Internal circuit IP 54

Supply includes: Nano-coated condenser
Integral electric condensate evaporation
Fully wired ready for connection (plug-in terminal strip)
Drilling template
Assembly parts

Packs of: 1 pc(s).

EAN: 4028177323117

eCl@ss 5.1: 27180704

eCl@ss 7.0: 27180704

Product features

**Total cooling output
to DIN EN 14511:** L 35 L 35 at 50 Hz: 2.55 kW
L 35 L 35 at 60 Hz: 2.71 kW
L 35 L 50 at 50 Hz: 1.89 kW
L 35 L 50 at 60 Hz: 1.97 kW

Air throughput (unimpeded air flow):	External circuit: 1230 m³/h Internal circuit: 1230 m³/h
Rated operating voltage:	230 V, 1~, 50 Hz/60 Hz
Dimensions:	Width: 400 mm Height: 1580 mm Depth: 295 mm
Temperature control:	e-Comfort controller (factory setting +35°C)
Temperature range:	Operation (environment): +10°C...+55°C Setting range: +20°C...+55°C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 950 g
Power consumption Pel:	L 35 L 35 at 50 Hz: 1.21 kW L 35 L 35 at 60 Hz: 1.35 kW L 35 L 50 at 50 Hz: 1.41 kW L 35 L 50 at 60 Hz: 1.64 kW
Rated current (max.):	At 50 Hz: 8.2 A At 60 Hz: 9.3 A
Start-up current max.:	At 50 Hz: 20 A At 60 Hz: 24 A
Pre-fuse:	Miniature circuit-breaker/fuse: 16 A
Permissible operating pressure (p. max.):	28 bar
Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511:	2.11
Weight:	69 kg

Approvals

Approvals:  [Approval overview \(EN\)](#)
 [CSA \(EN\)](#)
 [TUV-Geprüfte Leistung \(EN, DE\)](#)
 [TUV-Geprüfte Sicherheit \(EN, DE\)](#)
 [UR + C-UR \(EN\)](#)

Declarations:  [Declaration of conformity \(EN, DE\)](#)

Downloads

Data sheets:  [Safety data sheet \(EN\)](#)
 [Technical details \(EN\)](#)
 [Technical system catalogue \(DE\)](#)

Documentation:

 Instructions
2 EN

CAD drawings:

Request

Rittal – The System.

Faster – better – everywhere.

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG
Postfach 1662 · D-35726 Herborn
Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319
E-Mail: info@rittal.com · www.rittal.com

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

