

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

## PRODUCT DATA SHEET

### Bridge

**Code : 1303001T**

#### PRODUCT FAMILY

Outdoor Residential for direct wall fixing, complete with spherical diffuser Ø150mm, Ø200mm, Ø250mm (IP44).

#### MATERIAL CHARACTERISTICS

Bracket and wall fixing base in thermo-setting resin (BMC), black colour

Spherical diffuser in white, transparent, prismatic transparent, smoked and prismatic smoked PMMA with a diameter of Ø150mm, Ø200mm or Ø250mm.

Colours: Black-White, Black-Transparent, Black-Smoked.

Screws in stainless steel A2 .

#### LIGHTING CHARACTERISTICS

Lamp is in a fixed position

#### WIRING CHARACTERISTICS

Terminal for power supply cables 2.5mmq

Fitting designed for FBT lamp E27 lamp holder supply tension 220-240V 50-60Hz

#### INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

Base for wall fixing for horizontal or inclined installation, suitable for uplight or downlight; fixed with two screws (not supplied)

Ordinary maintenance by turning and removing the diffuser with bayonet neck

#### MEASUREMENT CHARACTERISTICS


Fixture length 228mm (Diffuser Ø150mm)

Fixture length 253mm (Diffuser Ø200mm)

ixture length 278mm (Diffuser Ø250mm)

#### Details

- Conformity with CEE directives
- Double insulation/class II
- Mounting on normal flammable surface
- Resistant to atmospheric agents
- Inalterable to ultraviolet radiations
- IP 44



230V 50Hz 8W E27

