

## **Product Specification Sheet**



## **Technical Information**

Instant Start:	0-100% in lt1s
Output Voltage:	DC 30-42V
Watts:	36
Lumens:	4320
Shape:	Square
Input Current:	0.2A
Beam Angle:	120
Output Current:	860mA
Unit Color:	White
Body Type:	Aluminium + PMMA + PC

## **Features**

- Compare with incandescent, it can save over 80% electric cost
- Contemporary & Elegant Design
- Higher Light Transmission Rate
- Easy to install Plug and play version
- Dimmable options available
  - High quality power driver ensures reliable lifetime
  - Controlled Glare rating values for comfortable commercial applications
  - Range of Sizes to suit different workspaces
  - Instant Start 0-100% in
  - No flickering, No U.V Radiation
  - No Lead or Mercury content hence Environment friendly
  - Application Office, Conference Room, Showroom, Lobby, Cabin, Kitchen etc



Suitable & Recommended for maximum daily use of 10-12 hours, usage beyond this would void the warranty

## Packaging

Unit Details		Listing Details	
Gross Weight(GW) Kgs	21.7	EAN Code	3800157622141
Length(Box)mm	130	Commodity Code	9405403990
Width(Box)mm	620		
Height(Box)mm	660		
Unit CBM	0.053196		
Master Box Packaging			
Inner Box Qty	1		
Master Box Qty (Pcs Per Carton)	6		
Qty Per Pallet	20		

