

40W LED Surface/Recessed Panel 6500K

SKU: 64521 | VT: VT-6142



[Contact us](#)

Product benefits

- Ultra Slim, Contemporary & Elegant Design
- Higher Light Transmission Rate
- Exterior shell, cannot be easily damaged
- No infrared, does not attract flies
- Easy to install
- No Lead or Mercury content
- Environment friendly
- Dimmable options available in selected models

Applications

- Office Lighting
- Conference Halls
- Hospitals
- Hotels
- Shopping Malls
- Showroom and lobby cabin etc.

Kitchen and Domestic Lighting

Specifications

General Information

LED Type

SMD

Lifespan

20 000 hrs

Electrical Data

Wattage

40W

Voltage

AC: 200-240V

Frequency

50/60Hz

Power Factor

>0.9

Light technical data**Light color**

White

Color Temperature

6400K

Luminous flux

4000 lm

Color Rendering Index CRI

>80

Beam angle

120 °

Body details**Material**

Aluminium+PMMA

Shape

Square

Body Colour

White

Type

Surface/Recessed

Capabilities**Dimmable**

No

IP Rating

IP20

Starting Time 100% ON

0.001 sec (instant on)

Color stability

<6

Declared peak intensity in candelas (cd)

/

On/Off cycles

>10000

Working conditions

Not suitable for use in extreme conditions. Normal working conditions is -20° +45°

Dimensions**Size**

595 x 595 x 29 mm

Product Data**Order code**

6452

Product code

VT-6142

Items per pack

1

Item Weight

2,15

Item Volume

0.0144

Items per box

6

EAN Code

3800157636438