

Product Specification Sheet



Technical Information

| Instant Start: | 0-100% in lt1s |
|----------------|----------------|
| Watts: | 15 |
| Lumens: | 1500 |
| hape: | Round |
| am Angle: | 120 |
| Color: | White |
| dy Type: | Aluminium |
| ong life: | 20,000 Hours |
| LED Chip Type: | SMD |

Features

- Compare with incandescent, it can save over 80% electric cost
- Contemporary & Elegant Design
 - Higher Light Transmission Rate
 - Easy to install Plug and play version
 - Dimmable options available
 - High quality power driver ensures reliable lifetime
 - Controlled Glare rating values for comfortable commercial applications
 - Range of Sizes to suit different workspaces
 - Instant Start 0-100% in
 - No flickering, No U.V Radiation
 - No Lead or Mercury content hence Environment friendly
 - Application Office, Conference Room, Showroom, Lobby, Cabin, Kitchen etc



Suitable & Recommended for maximum daily use of 10-12 hours, usage beyond this would void the warranty

Packaging

| Unit Details | | Listing Details | |
|---------------------------------|-----------|-----------------|---------------|
| Gross Weight(GW) Kgs | 1 | EAN Code | 3800157602624 |
| Length(Box)mm | 240 | Commodity Code | 9405403990 |
| Width(Box)mm | 240 | | |
| Height(Box)mm | 75 | | |
| Unit CBM | 0.0063948 | | |
| Master Box Packaging | | | |
| Master Box Qty (Pcs Per Carton) | 20 | | |
| Qty Per Pallet | 240 | | |
| | | | |

