

Product Specification Sheet



| Instant Start: | 0-100% in lt1s | lt1s | IP Rating: | IP20 |
|----------------|----------------|------|---|--------------|
| Watts: | 10 | | Dimmable: | No |
| Lumens: | 900 | | Warranty (Years): 2 PF: >0.6 CRI: >80 | |
| Beam Angle: | 120 | | | |
| Unit Color: | White | | | |
| Body Type: | Aluminium + PC | + PC | Operation Temperature: | -25 to +50°c |
| Long life: | 20,000 Hours | burs | Input Power: AC:85-265V,50/60Hz | |
| LED Chip Type: | SMD | | Sensor Compatibility: | Yes |

Features

- Multi-purpose LED Wall fitting Tube
- Easy installation and Maintenance
- Efficient High quality LED Chips & Integrated Driver
- ~~~~ PC Diffuser for Optimized light distribution and ambiance
 - Aluminum structure with Elegant white finish
 - Applications Residential, Commercial and many more



Suitable & Recommended for maximum daily use of 10-12 hours, usage beyond this would void the warranty

Packaging

| Unit Details | |
|---------------------------------|-----------|
| Gross Weight(GW) Kgs | 0.24 |
| Length(Box)mm | 630 |
| Width(Box)mm | 45 |
| Height(Box)mm | 30 |
| Unit CBM | 0.0008478 |
| Master Box Packaging | |
| Master Box Qty (Pcs Per Carton) | 25 |
| | |

