

Product Specification Sheet



VT-8030 PIR CEILING SENSOR WITH MOVING HEAD

Beam Angle 360

Dimensions 98x73x82mm

SKU:5091



Technical Information

Beam Angle:	360
Ambient Light:	
Detection Distance:	Max. 8m(
Detection Motion Speed:	0.6-1.5m/s
Rated Load:	Max. 400W
Time Delay:	Min. 10sec±3sec, Max. 15min±2min
Detection Range:	360°
Unit Color:	White

Body Type: PC
Sensor Type: Infrared
Long life: 20,000 Hours
IP Rating: IP20
Dimmable: No
Warranty (Years): 2
Input Power: AC:220-240V,50Hz



Features

Downlight series built with High quality COB LED chip

Premium Quality Power Driver with high quality power factor correction

Die cast aluminium housing with heat sink for optimum thermal mangement

Multi faceted aluminium reflector for optimum light intensity

Lumen efficiency range starting from 65lm/W up to 120LM/W

✓ Non-Flickering - No UV Radiation

Low Maintenance and Easy Installation

Available from 3W to 40W

Applications - Residential, Showrooms, Hotels & Boutiques etc



Suitable & Recommended for maximum daily use of 10-12 hours, usage beyond this would void the warranty

Packaging

Unit Details

 Gross Weight(GW) Kgs
 0.13

 Unit CBM
 0.00068

Master Box Packaging

 Master Box Qty (Pcs Per Carton)
 50

 Qty Per Pallet
 2000

Listing Details

EAN Code 3800157609227



