




Dane do zamówienia

	Znamionowy prąd pracy AC-3		Max moc silnika indukcyjnego 50–60 Hz AC-3				Max czas przełączania s	Typ Nr artykułu	Opak.	
	400 V		230 V	400 V	500 V	690 V				
	I _e A		P kW	P kW	P kW	P kW				
Zestawy gwiazda-trójkąt SDAINL										
Częstość łączeń: max 30 rozruchów na godzinę										
	12		4	5,5	5,5	–	< 30	SDAINLEM(230V50Hz) 051840	1 szt.	
	12		3	5,5	5,5	5,5	< 20	SDAINLM12(230V50Hz) 278286		
	12		3	5,5	5,5	5,5	< 20	SDAINLM12(400V50Hz) 101380		
	12		3	5,5	5,5	5,5	< 20	SDAINLM12(24VDC) 100416		
	16		4	7,5	7,5	7,5	< 20	SDAINLM16(230V50Hz) 278311		
	16		4	7,5	7,5	7,5	< 20	SDAINLM16(400V50Hz) 101381		
	16		4	7,5	7,5	7,5	< 20	SDAINLM16(24VDC) 100417		
	22		5,5	11	11	11	< 20	SDAINLM22(230V50Hz) 278336		
	22		5,5	11	11	11	< 20	SDAINLM22(400V50Hz) 101382		
	22		5,5	11	11	11	< 20	SDAINLM22(24VDC) 100418		
		30		7,5	15	18,5	18,5	< 20	SDAINLM30(230V50Hz) 278361	
30			7,5	15	18,5	18,5	< 20	SDAINLM30(400V50Hz) 101383		
30			7,5	15	18,5	18,5	< 20	SDAINLM30(RDC24) 100419		
45			11	22	30	22	< 20	SDAINLM45(230V50Hz) 278386		
45			11	22	30	22	< 20	SDAINLM45(400V50Hz) 101384		
45			11	22	30	22	< 20	SDAINLM45(RDC24) 100420		
55			15	30	37	30	< 20	SDAINLM55(230V50Hz) 278411		
55			15	30	37	30	< 20	SDAINLM55(400V50Hz) 101385		
55			15	30	37	30	< 20	SDAINLM55(RDC24) 100421		
70			18,5	37	45	37	< 20	SDAINLM70(230V50Hz) 239895		
70			18,5	37	45	37	< 20	SDAINLM70(400V50Hz) 101386		
90			22	45	55	45	< 20	SDAINLM90(230V50Hz) 239937		
115			30	55	75	55	< 20	SDAINLM115(230V50Hz) 239963		
140			37	75	90	90	< 20	SDAINLM140(230V50Hz) 240009		
165			45	90	110	132	< 20	SDAINLM165(230V50Hz) 240035		
200			55	110	132	160	< 20	SDAINLM200(230V50Hz) 101010		
260		75	132	160	160	< 20	SDAINLM260(230V50Hz) 101031			