



Actinic BL TL-D(K) Secura

Actinic BL TL-D TL-DK Secura 36W/10 1SL/25

With an optimized spectrum matching the eye sensitivity of the housefly, Actinic BL TL-D(K) Secura lamps are perfect for attracting insects. They have virtually no UV-B output, and so are perfectly safe. In addition, they have a special "Secura" sleeve that keeps all glass and components together in the case of accidental breakage. This eliminates the risk of glass splinters showering down on food preparation areas, for example. And that is why it meets the strict HACCP requirements. What's more, with the lowest mercury content in the industry and being 100% lead-free, these lamps represent a very good environmental choice.

Product data

General Information		Voltage (Nom) 50 V	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	Approval and Application	
Main Application	Reprography (R)	Mercury (Hg) Content (Nom)	8.0 mg
Life to 50% Failures (Nom)	9000 h	UV	
Useful Life (Nom)	5000 h	UV-B/UV-A (IEC)	0.2 %
Light Technical		UV-A Radiation 100Hr (IEC)	8.8 W
Color Code	10	Product Data	
Color Designation	Actinic	Full product code	872790086085600
Chromaticity Coordinate X (Nom)	225	Order product name	Actinic BL TL-D TL-DK Secura 36W/10 1SL/25
Chromaticity Coordinate Y (Nom)	230	EAN/UPC - Product	8727900860856
UV Depreciation at 2000 h	20 %	Order code	928019801003
UV Depreciation at 5000 h	30 %	Numerator - Quantity Per Pack	1
Operating and Electrical		Numerator - Packs per outer box	25
Power (Rated) (Nom)	36 W	Material Nr. (12NC)	928019801003
Lamp Current (Nom)	0.865 A		

Actinic BL TL-D(K) Secura

Net Weight (Piece)	127.500 g
--------------------	-----------

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing

Product	D (max)	A (max)	B (max)	B (min)	C (max)
Actinic BL TL-D TL-DK	28 mm	589.8 mm	596.9 mm	594.5 mm	604 mm
Secura 36W/10 1SL/25					

TL-DK Secura 36W/10

Photometric data

Lightcolor /10

Lightcolor /10

