

## KOŃCÓWKI Cu Z PRZEWĘŻONYM PRZYŁOŻENIEM

do zakańczania żył kabli Cu montowanych w aparaturze rozdzielczej

**Materiał:** miedź

**Powierzchnia:** cynowana galwanicznie



| Oznaczenie      | Przekrój mm <sup>2</sup> | Szerokość |
|-----------------|--------------------------|-----------|
| 10 x 5 KU-L-A   | 10                       | 9 mm      |
| 16 x 5 KU-L-A   | 16                       | 9 mm      |
| 25 x 5 KU-L-A   | 25                       | 9 mm      |
| 35 x 6 KU-L-A   | 35                       | 11,5 mm   |
| 50 x 6 KU-L-A   | 50                       | 11,5 mm   |
| 70 x 6 KU-L-A   | 70                       | 11,5 mm   |
| 95 x 8 KU-L-A   | 95                       | 15,5 mm   |
| 120 x 8 KU-L-A  | 120                      | 19,0 mm   |
| 120 x 10 KU-L-A | 120                      | 19,0 mm   |
| 150 x 8 KU-L-A  | 150                      | 19,0 mm   |
| 150 x 10 KU-L-A | 150                      | 19,0 mm   |
| 185 x 10 KU-L-A | 185                      | 24,5 mm   |
| 240 x 10 KU-L-A | 240                      | 31,0 mm   |
| 240 x 12 KU-L-A | 240                      | 31,0 mm   |



## KOŃCÓWKI Cu

wg DIN 46235

do zakańczania żył kabli Cu do 36 kV

**Materiał:** miedź

**Powierzchnia:** metaliczna



| Oznaczenie | Przekrój mm <sup>2</sup> |
|------------|--------------------------|
| 6 x 5 KU   | 6                        |
| 6 x 6 KU   |                          |
| 10 x 5 KU  | 10                       |
| 10 x 6 KU  |                          |
| 16 x 6 KU  | 16                       |
| 16 x 8 KU  |                          |
| 16 x 10 KU |                          |
| 16 x 12 KU |                          |
| 25 x 6 KU  | 25                       |
| 25 x 8 KU  |                          |
| 25 x 10 KU |                          |
| 25 x 12 KU |                          |
| 35 x 6 KU  | 35                       |
| 35 x 8 KU  |                          |
| 35 x 10 KU |                          |
| 35 x 12 KU |                          |
| 50 x 8 KU  | 50                       |
| 50 x 10 KU |                          |
| 50 x 12 KU |                          |
| 70 x 8 KU  | 70                       |
| 70 x 10 KU |                          |
| 70 x 12 KU |                          |
| 70 x 16 KU |                          |
| 95 x 10 KU | 95                       |
| 95 x 12 KU |                          |
| 95 x 16 KU |                          |

| Oznaczenie   | Przekrój mm <sup>2</sup> |
|--------------|--------------------------|
| 120 x 10 KU  | 120                      |
| 120 x 12 KU  |                          |
| 120 x 16 KU  |                          |
| 150 x 10 KU  | 150                      |
| 150 x 12 KU  |                          |
| 150 x 16 KU  |                          |
| 150 x 20 KU  |                          |
| 185 x 10 KU  | 185                      |
| 185 x 12 KU  |                          |
| 185 x 16 KU  |                          |
| 185 x 20 KU  |                          |
| 240 x 12 KU  | 240                      |
| 240 x 16 KU  |                          |
| 240 x 20 KU  |                          |
| 300 x 12 KU  | 300                      |
| 300 x 16 KU  |                          |
| 300 x 20 KU  |                          |
| 400 x 12 KU  | 400                      |
| 400 x 16 KU  |                          |
| 400 x 20 KU  |                          |
| 500 x 12 KU  | 500                      |
| 500 x 16 KU  |                          |
| 500 x 20 KU  |                          |
| 625 x 16 KU  | 625                      |
| 625 x 20 KU  |                          |
| 800 x 20 KU  | 800                      |
| 1000 x 20 KU | 1000                     |

## KOŃCÓWKI Cu CYNOWANE

wg DIN 46235

do zakańczania żył kabli Cu do 36 kV

**Materiał:** miedź

**Powierzchnia:** cynowana galwanicznie



| Oznaczenie    | Przekrój mm <sup>2</sup> |
|---------------|--------------------------|
| 6 x 5 KU-V    | 6                        |
| 6 x 6 KU-V    |                          |
| 10 x 5 KU-V   | 10                       |
| 10 x 6 KU-V   |                          |
| 16 x 6 KU-V   | 16                       |
| 16 x 8 KU-V   |                          |
| 16 x 10 KU-V  |                          |
| 16 x 12 KU-V  |                          |
| 25 x 6 KU-V   | 25                       |
| 25 x 8 KU-V   |                          |
| 25 x 10 KU-V  |                          |
| 25 x 12 KU-V  |                          |
| 35 x 6 KU-V   | 35                       |
| 35 x 8 KU-V   |                          |
| 35 x 10 KU-V  |                          |
| 35 x 12 KU-V  |                          |
| 50 x 8 KU-V   | 50                       |
| 50 x 10 KU-V  |                          |
| 50 x 12 KU-V  |                          |
| 70 x 8 KU-V   | 70                       |
| 70 x 10 KU-V  |                          |
| 70 x 12 KU-V  |                          |
| 70 x 16 KU-V  |                          |
| 95 x 10 KU-V  | 95                       |
| 95 x 12 KU-V  |                          |
| 95 x 16 KU-V  |                          |
| 120 x 10 KU-V | 120                      |
| 120 x 12 KU-V |                          |
| 120 x 16 KU-V |                          |
| 150 x 10 KU-V | 150                      |
| 150 x 12 KU-V |                          |
| 150 x 16 KU-V |                          |
| 150 x 20 KU-V |                          |
| 185 x 10 KU-V | 185                      |
| 185 x 12 KU-V |                          |
| 185 x 16 KU-V |                          |
| 185 x 20 KU-V |                          |

| Oznaczenie     | Przekrój mm <sup>2</sup> |
|----------------|--------------------------|
| 240 x 12 KU-V  | 240                      |
| 240 x 16 KU-V  |                          |
| 240 x 20 KU-V  |                          |
| 300 x 12 KU-V  | 300                      |
| 300 x 16 KU-V  |                          |
| 300 x 20 KU-V  |                          |
| 400 x 12 KU-V  | 400                      |
| 400 x 16 KU-V  |                          |
| 400 x 20 KU-V  |                          |
| 500 x 12 KU-V  | 500                      |
| 500 x 16 KU-V  |                          |
| 500 x 20 KU-V  |                          |
| 625 x 16 KU-V  | 625                      |
| 625 x 20 KU-V  |                          |
| 800 x 20 KU-V  | 800                      |
| 1000 x 20 KU-V | 1000                     |

## KOŃCÓWKI Cu CYNOWANE

wg DIN 46235

do zakańczania żył kabli Cu do 36 kV

**Materiał:** miedź

**Powierzchnia:** cynowana galwanicznie



| Oznaczenie    | Przekrój mm <sup>2</sup> |
|---------------|--------------------------|
| 10 x 5 KU-W   | 10                       |
| 10 x 6 KU-W   |                          |
| 16 x 6 KU-W   | 16                       |
| 16 x 8 KU-W   |                          |
| 16 x 10 KU-W  |                          |
| 25 x 6 KU-W   | 25                       |
| 25 x 8 KU-W   |                          |
| 25 x 10 KU-W  |                          |
| 25 x 12 KU-W  |                          |
| 35 x 8 KU-W   | 35                       |
| 35 x 10 KU-W  |                          |
| 35 x 12 KU-W  |                          |
| 50 x 8 KU-W   | 50                       |
| 50 x 10 KU-W  |                          |
| 50 x 12 KU-W  |                          |
| 70 x 8 KU-W   | 70                       |
| 70 x 10 KU-W  |                          |
| 70 x 12 KU-W  |                          |
| 95 x 8 KU-W   | 95                       |
| 95 x 10 KU-W  |                          |
| 95 x 12 KU-W  |                          |
| 120 x 10 KU-W | 120                      |
| 120 x 12 KU-W |                          |
| 120 x 16 KU-W |                          |
| 150 x 12 KU-W | 150                      |
| 150 x 16 KU-W |                          |
| 185 x 12 KU-W | 185                      |
| 185 x 16 KU-W |                          |
| 240 x 12 KU-W | 240                      |
| 240 x 16 KU-W |                          |
| 300 x 12 KU-W | 300                      |
| 300 x 16 KU-W |                          |