

**NEW**

## DUOCUT 12 cable shears

Innovative cable shears for copper and aluminium cables with multi-component VDE case. Particularly suitable for exact cutting of cables without deformation. The handles of the shears can be opened up to 140°, consequently a longitudinal cut is possible. VDE/GS approved, according to IEC 60900 and VDE 0682 / part 201. Weight: 300 g.

### Highlight:

The two-stage cutting zone:

1. Large blade for sheathed cables up to max. 12 mm ø
2. Small blade for single conductors up to max. 4 mm ø



			200	1	12 0112	
--	--	--	-----	---	---------	--

## VDE cable shears

For copper and aluminium cables, very good cutting performance, made from case-hardened 5 mm flat tool steel, precision ground cutting edges, finely bronzed, 2-component plastic handle sleeves, with special blade for fine-wire cables up to ø 18 mm

- VDE / GS approved
- According to IEC 60900 and VDE 0682 / part 201
- Product conforms to the current Product Safety Act (ProdSG)

**NEW**

for cable ø	solid mm <sup>2</sup>	flexible mm <sup>2</sup>				
18 mm	16	50	180	1	12 0114	

## Cable shears

For copper and aluminium cables, excellent cutting performance, made from case-hardened 5 mm flat tool steel, precision ground cutting edges, finely bronzed, 2-component plastic handle sleeves, with special blade for fine-wire cables up to ø 18 mm



for cable ø	solid mm <sup>2</sup>	flexible mm <sup>2</sup>				
18 mm	16	50	180	1	12 0116	

## One-hand cable shears

For copper and aluminium cables, excellent cutting performance, smooth cut with no deformation, die-forged, precision ground, adjustable screw joint, 2-component plastic handle sleeves



for cable ø	solid mm <sup>2</sup>	flexible mm <sup>2</sup>				
16 mm	16	50	160	1	12 0104	

## 1000 V one-hand cable shears

For copper and aluminium cables, excellent cutting performance, smooth cut without deformation with double dip-coated special insulation



for cable ø	solid mm <sup>2</sup>	flexible mm <sup>2</sup>				
16 mm	16	50	160	1	12 0206	

## One-hand cable shears

for copper and aluminium cables, excellent cutting performance, smooth cut without deformation, die-forged, precision ground, adjustable screw joint, 2-component plastic handle sleeves



for cable ø	solid mm <sup>2</sup>	flexible mm <sup>2</sup>				
25 mm	25	70	200	1	12 0100	