



 220-240 AC	 50/60	 110	 ≥20000	 15000	 ≤ 6x Macadam	 Ra ≥80
 SMD		 IP 44/20		 5+25		
	 0,05	 0,75	 0,5m			



						
ROUND A V2LED12W-NW-SN	27218	12	nikiel satynowy	780	110	4000
ROUND A V2LED18W-NW-SN	27219	18	nikiel satynowy	1250	110	4000
ROUND A V2LED24W-NW-SN	27220	24	nikiel satynowy	1700	110	4000
ROUND A V2LED6W-NW-SN	27221	6	nikiel satynowy	300	110	4000
ROUND A V2LED12W-NW-SR	28930	12	srebrny	660	110	4000
ROUND A V2LED12W-NW-W	28931	12	biały	780	110	4000
ROUND A V2LED12W-WW-W	28932	12	biały	720	110	3000
ROUND A V2LED18W-NW-SR	28933	18	srebrny	1080	110	4000
ROUND A V2LED18W-NW-W	28934	18	biały	1260	110	4000
ROUND A V2LED18W-WW-W	28935	18	biały	1200	110	3000
ROUND A V2LED24W-NW-W	28936	24	biały	1680	110	4000
ROUND A V2LED6W-NW-W	28937	6	biały	330	110	4000
ROUND A V2LED6W-WW-W	28938	6	biały	300	110	3000



- Dokument utworzono: 17.05.2019, 10:44

Zastrzega się możliwość wprowadzenia zmian technicznych. Dane zawarte w tym katalogu nie są prawnie wiążące.

ROUNDA V2LED

Oprawa typu downlight



ROUNDA V2LED12W-NW-SN



ROUNDA V2LED18W-NW-SN



ROUNDA V2LED24W-NW-SN



ROUNDA V2LED6W-NW-SN



ROUNDA V2LED12W-NW-SR



ROUNDA V2LED12W-NW-W



ROUNDA V2LED12W-WW-W



ROUNDA V2LED18W-NW-SR



ROUND A V2LED

Oprawa typu downlight

ROUND A V2LED18W-NW-W


ROUND A V2LED18W-WW-W

ROUND A V2LED24W-NW-W


ROUND A V2LED6W-NW-W




ROUND A V2LED6W-WW-W




ROUND A V2LED12W



ROUND A V2LED18W



ROUND A V2LED24W



ROUND A V2LED6W