



SPECYFIKACJA TECHNICZNA

| | |
|--------------------------|-------------------|
| Moc: | 36 |
| Lumeny: | 3960 |
| Napięcie wejściowe: | AC:220-240V, 50Hz |
| Żywotność: | 20,000 Hours |
| Kolor urządzenia: | White |
| Materiał: | PP+FE |
| PF: | >0.9 |
| Typ modułu LED: | SMD |
| CRI: | >80 |
| Zakres temperatur pracy: | -20°C to +40°C |
| Ściemnianie: | No |
| Kąt świecenia: | 110° |
| Temperatura barwowa: | 4000K |
| Wymiary opakowania: | 595x595x30mm |
| Lumeny na Wat: | 110 |

SZCZEGÓŁY PRODUKTU

Kod EAN: 3800170202054

OPAKOWANIE

Waga produktu kg: 2.33
 Jednostka CBM: 0.017462
 Wymiary opakowania: 595x595x30mm

OPAKOWANIE ZBIORCZE

Ilość w Kartonie: 6



2 IN 1 PANELS | LED LIGHTING

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide an extended multi-year warranty on our products, as well as detailed support.

FEATURES

- Powerful LED light source with lumen efficiency of 110 LM/W
- Backlit panel with 2IN1 Recessed and Surfaced Installation
- Fitted with high efficiency SMD LED Chips
- Strong and sturdy PP+FE body
- Easy to connect driver for quicker installation
- Suitable for offices, conference rooms, showrooms, lobbies, cabins, kitchens etc.

