

Styczniki DILM o mocy 18,5-37 kW

	Prąd	Moc	Napięcie sterujące 230 V 50 HZ, 240 V 60 HZ		Napięcie sterujące 24 V DC	
	AC3 380 V/400 V					
	A	kW	Typ	Nr zam.	Typ	Nr zam.
	40	18,5	DILM40-EA(230V50HZ,240V60HZ)	190009	DILM40-EA(RDC24)	190010
	50	22	DILM50-EA(230V50HZ,240V60HZ)	190011	DILM50-EA(RDC24)	190012
	65	30	DILM65-EA(230V50HZ,240V60HZ)	190013	DILM65-EA(RDC24)	190014
	72	37	DILM72-EA(230V50HZ,240V60HZ)	189919	DILM72-EA(RDC24)	189920

Akcesoria

Styki boczne, wewnętrzne

Ilość i rodzaj styków	Typ	Nr zam.
1 Z 1 R	DILM1000-XHI11-SI	278425

Styki czołowe

Ilość i rodzaj styków	Typ	Nr zam.
2 Z	DILM150-XHI20	277945
1 Z 1 R	DILM150-XHI11	277946
4 Z	DILM150-XHI40	277948
3 Z 1 R	DILM150-XHI31	277949
2 Z 2 R	DILM150-XHI22	277950
1 Z 3 R	DILM150-XHI13	277951

Przełączniki przeciążeniowe ZB65

Zakres nastaw [A]	Typ	Nr zam.
10 - 16	ZB65-16	278456
16 - 24	ZB65-24	278457
24 - 40	ZB65-40	278458
40 - 57	ZB65-57	278459
50 - 65	ZB65-65	278460
65 - 75	ZB65-75	108792

Wymiary

DILM40-DILM72

